# Gigaset DESK 200

### The space-saving, corded desk and wall phone

### **Highlights**

- Space-saving due to particularly narrow design
- o Easy wall mounting possible
- Power supply via telephone line, no separate power supply necessary
- o Ten speed dial keys
- Hearing aid compatible
- Redial
- LED call signaling
- Suitable for operation with telephone systems
- o DTMF / pulse dialing adjustable
- Flash function adjustable



The corded desk and wall phone Gigaset DESK 200 impresses with its slim, space-saving shape and is ideal for use at home or in the office.

#### Particularly space-saving & easy wall mounting

The Gigaset DESK 200 combines all important telephony functions with a particularly slim design. It is therefore ideal as a space-saving desk phone or can be quickly and easily mounted on the wall.

#### Power supply via the telephone line

The Gigaset DESK 200 does not require a separate power supply unit. Power is supplied directly via the telephone line. Commissioning is therefore particularly simple: connect the Gigaset DESK 200 to the telephone socket (public network, PBX or gateway) - and the phone is ready for use.

#### **Quickly connected**

Up to ten phone numbers can be stored as speed dials, allowing you to quickly connect to the people you talk to frequently. The speed-dial numbers are noted on the enclosed paper inlay and are thus always in view.

#### Visual and acoustic call signaling

The melody and volume of the Gigaset DESK 200 can be conveniently set. Three different melodies can be selected, which can be set to three different volume levels. In addition, the optical call signaling via the LED on the handset helps to ensure that no call is missed even in particularly noisy environments.



## **Technical Specifications**

| Ordering Information    | Colour                        | black  |       |        |        |
|-------------------------|-------------------------------|--|-------|--------|--------|
| -                       |                               |  |       |        |        |
|                         | Ringtone output               | Ring tone output with adjustable volume (3 levels)   |       |        |        |
| Audio                   | Volume                        | Adjustable handset volume (2 levels)   |       |        |        |
|                         | Hearing aid compatible        | Hearing aid compatible   |       |        |        |
|                         |                               | i roaming and  |       |        |        |
| Keyboard                | Keys                          | <ul><li>10 number keys</li><li>Volume button</li><li>Menu key</li><li>Redial button</li><li>Mute button</li></ul>  |       |        |        |
|                         | Functions                     | <ul> <li>R-key (flash time adjustable via slide switch)</li> <li>Programmable speed dialling keys (keys 0 - 9)</li> </ul>  |       |        |        |
|                         |                               |  |       |        |        |
| Functions               | Desk operation                | yes  |       |        |        |
|                         | Wall mountable                | yes  |       |        |        |
|                         |                               |  |       |        |        |
| Signalling & display    | Optical call display          | LED call signaling on the handset  |       |        |        |
| indications             | Ringtones                     | 3 adjustable ringtones   |       |        |        |
|                         | -                             | -  |       |        |        |
| Dial functions          | Redial                        | 1 redial entry with up to 31 characters  |       |        |        |
|                         | Dialling procedure            | Pulse dialing method (IWV)     Multi-frequency dialling (DTMF)   |       |        |        |
|                         |                               |  | , , , | ,      |        |
| Power supply            | Analogue telephone connection | Power is supplied to the telephone via the telephone line. A separate power supply unit is not required. Due to its own power supply, it is possible to make calls even in the event of a power failure. |       |        |        |
|                         |                               |  |       |        |        |
| Connectivity            | Analogue telephone connection | Connection to an external telephone line (a/b)   |       |        |        |
|                         | Connection type               | Analogue   |       |        |        |
|                         | Connection options            | Suitable for operation on telephone systems  |       |        |        |
|                         | •                             | •  |       |        |        |
| Dimensions &<br>Weights | Device                        | Height   | Width | Depth  | Weight |
|                         | Desk phone                    | 57 mm  | 80 mm | 208 mm | 352 g  |
|                         | Telephone handset             | 47 mm  | 51 mm | 197 mm | 144 g  |
|                         | Handset cable                 |  |       |        | 38 g   |
|                         | 1                             | 1  | I .   | 1      |        |
| Scope Of Delivery       | 1x                            | Desk phone   |       |        |        |
|                         | 1x                            | Telephone connection cable   |       |        |        |
|                         | 1x                            | Short user guide   |       |        |        |
|                         | 1x                            | Handset connection cable   |       |        |        |
|                         |                               |  |       |        |        |

Herausgegeben von Gigaset Communications GmbH. Alle Rechte, Liefermöglichkeiten und Änderungen in Technik und Design vorbehalten.
Die in diesem Dokument verwendeten Produktnamen sind Warenzeichen oder eingetragene Warenzeichen ihrer jeweiligen Inhaber. ProDSION-DE-0221

Version 27.09.2022

